Bollards.

Characteristics

- Wide range of standard shapes, load ratings, materials, and anchor systems
- Strong & long lasting designs
- Standard epoxy coating (NDFT 450 μ)
- Large line angles possible
- Special designs available upon request

Applications

- Container & Bulk Terminals
- Oil & Gas Terminals
- General Cargo Terminals
- Cruise Terminals, Ferry & RoRo Terminals
- Navy
- Leisure craft (customized)

T HEAD

| Туре | Capacity | Anchors |
|--------|----------|---------|
| FT 10 | 10 Tons | 4 x M24 |
| FT 15 | 15 Tons | 4 x M24 |
| FT 20 | 20 Tons | 5 x M24 |
| FT 30 | 30 Tons | 5 x M30 |
| FT 50 | 50 Tons | 5 x M36 |
| FT 75 | 75 Tons | 6 x M42 |
| FT 100 | 100 Tons | 7 x M42 |
| FT 125 | 125 Tons | 7 x M48 |
| FT 150 | 150 Tons | 7 x M48 |
| FT 200 | 200 Tons | 8 x M56 |
| FT 250 | 250 Tons | 8 x M56 |
| FT 300 | 300 Tons | 8 x M64 |

Also available as Double T Head



STAGHORN

| Туре | Capacity | Anchors |
|---------|----------|---------|
| FSH 10 | 10 Tons | 4 x M24 |
| FSH 15 | 15 Tons | 4 x M24 |
| FSH 20 | 20 Tons | 5 x M24 |
| FSH 30 | 30 Tons | 5 x M30 |
| FSH 50 | 50 Tons | 5 x M36 |
| FSH 75 | 75 Tons | 6 x M42 |
| FSH 100 | 100 Tons | 7 x M42 |
| FSH 125 | 125 Tons | 7 x M48 |
| FSH 150 | 150 Tons | 7 x M48 |
| FSH 200 | 200 Tons | 8 x M56 |

Higher capacity available upon request



Hole for concrete infill omitted



T Head Bollard



Staghorn Bollard

For detailed information on design, load angles, anchor types, materials as well as good practice installation and application, please refer to the dedicated SFT bollard manual.

SINGLE BITT

| Туре | Capacity | Anchors |
|---------|----------|---------|
| FSB 10 | 10 Tons | 4 x M24 |
| FSB 15 | 15 Tons | 4 x M24 |
| FSB 20 | 20 Tons | 5 x M24 |
| FSB 30 | 30 Tons | 5 x M30 |
| FSB 50 | 50 Tons | 6 x M36 |
| FSB 75 | 75 Tons | 6 x M42 |
| FSB 100 | 100 Tons | 7 x M48 |
| FSB 125 | 125 Tons | 7 x M48 |
| FSB 150 | 150 Tons | 7 x M56 |
| FSB 200 | 200 Tons | 8 x M56 |

Higher capacity available upon request





Single Bitt Bollard

DOUBLE BITT

| Туре | Capacity | Anchors |
|---------|----------|----------|
| FDB 20 | 10 Tons | 8 x M20 |
| FDB 35 | 15 Tons | 8 x M22 |
| FDB 50 | 20 Tons | 8 x M30 |
| FDB 75 | 30 Tons | 10 x M36 |
| FDB 100 | 50 Tons | 10 x M42 |
| FDB 125 | 75 Tons | 10 x M42 |
| FDB 150 | 100 Tons | 10 x M48 |
| FDB 200 | 125 Tons | 10 x M56 |

Higher capacity available upon request



Hole for concrete infill omitted



Double Bitt Bollard

SINGLE BITT 360°

Capacity available from 10 t - 200 t

KIDNEY Capacity available from 15 t - 200 t

FABRICATED/WELDED

Custom design

TRICORN Capacity available from 50 t – 150 t

CLEATS Sizes available from 610 mm – 1,372 mm









